



TIS 2000 PC Requirements

PC requirements:

Minimum:

- Pentium II 166 MHz Microprocessor or compatible.
- 32 MB RAM.
- 500MB of available hard drive space.
- 16X CD-ROM drive.
- One free USB port for GM Hardware lock.
- One free USB port for J2534 Pass-Thru device.
- Keyboard & Mouse.
- Graphics Card - 800x600, 256 colors.

Recommended:

- Pentium 500MHz Microprocessor or compatible and upwards.
- 512 MB RAM and upwards.
- 500MB of available hard drive space and upwards.
- 32X CD-ROM drive and upwards.
- One free USB port for GM Hardware lock.
- One free USB port for J2534 Pass-Thru device.
- Wireless connection for J2534 Pass-Thru device.
- Keyboard & Mouse.
- Graphics Card - 1024x768, 16-bit colors and upwards.

Operation System:

- Windows 98 SE or Windows NT4 (SP3) and upwards.

Hardware:

1. J2534 Pass-Thru device (EASE Diagnostics compatible) with USB cable.
2. TIS2000 Hardware Lock. Authorizes a PC to perform reprogramming using TIS2000.
3. In-Vehicle: DLC cables (BLACK and BLUE).
4. Off-Board: A set of GM Off-Board cables and a 12V DC / 1500mA power supply.
5. Off-Board Kent-Moore: A Kent-Moore unit, a DLC cable (BLACK) and a set of GM Off-Board Kent-Moore cables.



TIS 2000 PC Requirements

Software:

1. GM service Information. One year CD based software subscription containing technical information, including recalibration files for reprogramming and calibration history information.
2. GM Service Programming Assistant (SPA) software including GM Expertec SPS software (TIS 2000).
3. Access code to unlock SPA capabilities:
 - GM In-Vehicle reprogramming.
 - GM Off-Board reprogramming.
 - GM Body-Chassis controllers reprogramming.
 - Wireless.